

PORE MP 3000° K

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	76.0	83.2%
0-40	88.9	97.4%
0-60	91.3	99.9%
60-90	0.0	0.1%
70-100	0.0	0%
90-120	0.007	0%
0-90	91.3	100%
90-180	0.007	0%
0-180	91.3	100%

Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	13.8	15.1%	90-100	0.002	0%
10-20	32.7	35.8%	100-110	0.003	0%
20-30	29.5	32.3%	110-120	0.002	0%
30-40	12.9	14.2%	120-130	0.000	0%
40-50	2.3	2.5%	130-140	0.000	0%
50-60	0.0	0.1%	140-150	0.000	0%
60-70	0.0	0.0%	150-160	0.000	0%
70-80	0.0	0.0%	160-170	0.000	0%
80-90	0.005	0.0%	170-180	0.000	0%

Roadway Summary

Distribution:	Type	VS
Max Cd, 90 Deg Vert:		0.004
Max Cd, 80 to <90 Deg:		0.0
	Lumens	% Lamp
Downward Street Side:	56.0	61.3%
Downward House Side:	36.5	39.9%
Downward Total:	92.4	101.2%
Upward Street Side:	0.002	0%
Upward House Side:	0.004	0%
Upward Total:	0.007	0%
Total Lumens:	92.4	101.2%

LCS Table

BUG Rating	B0 - U1 - G0	
Forward Light	Lumens	Lumens %
Low(0-30):	44.5	48.8%
Medium(30-60):	11.4	12.5%
High(60-80):	0.0	0%
Very High(80-90):	0.004	0%
Back Light		
Low(0-30):	32.3	35.4%
Medium(30-60):	4.1	4.5%
High(60-80):	0.0	0%
Very High(80-90):	0.001	0%
Uplight		
Low(90-100):	0.002	0%
High(100-180):	0.005	0%
Trapped Light:	0.000	0%