

PORE MP 3000° K

Zonal Lumen Summary

Zone	Lumens	% Luminaire
0-30	18.6	35.6%
0-40	29.2	56%
0-60	44.3	84.9%
60-90	7.7	14.8%
70-100	3.5	6.7%
90-120	0.1	0.3%
0-90	52.1	99.7%
90-180	0.1	0.3%
0-180	52.2	100%

Lumens Per Zone

Zone	Lumens	% Total	Zone	Lumens	% Total
0-10	2.2	4.3%	90-100	0.1	0.3%
10-20	6.5	12.5%	100-110	0.005	0%
20-30	9.8	18.8%	110-120	0.003	0%
30-40	10.6	20.4%	120-130	0.000	0%
40-50	8.8	16.9%	130-140	0.000	0%
50-60	6.3	12.1%	140-150	0.000	0%
60-70	4.4	8.3%	150-160	0.000	0%
70-80	2.5	4.8%	160-170	0.000	0%
80-90	0.9	1.7%	170-180	0.000	0%

Roadway Summary

Distribution: TYPE I, VERY SHORT		
Max Cd, 90 Deg Vert:		0.9
Max Cd, 80 to <90 Deg:		5.0
	Lumens	% Lamp
Downward Street Side:	26.0	49.8%
Downward House Side:	26.2	50.2%
Downward Total:	52.2	100%
Upward Street Side:	0.1	0.1%
Upward House Side:	0.1	0.1%
Upward Total:	0.1	0.3%
Total Lumens:	52.3	100.2%

LCS Table

BUG Rating	B0 - U1 - G0	
	Lumens	Lumens %
Forward Light		
Low(0-30):	9.4	18%
Medium(30-60):	12.7	24.4%
High(60-80):	3.5	6.6%
Very High(80-90):	0.4	0.9%
Back Light		
Low(0-30):	9.2	17.7%
Medium(30-60):	13.1	25.1%
High(60-80):	3.4	6.5%
Very High(80-90):	0.4	0.8%
Uplight		
Low(90-100):	0.1	0.3%
High(100-180):	0.008	0%
Trapped Light:	0.000	0%